

RENEGADE™ 800 H.O. EFI



Renegade
800 H.O. EFI 4x4



Renegade
800 H.O. EFI X 4x4

SPECIFICATIONS

RENEGADE 800 H.O. EFI 4x4

	ENGINE	CHASSIS	DIMENSIONS	FEATURES	PACKAGE					
	Type Bore & Stroke Torque Fuel Delivery Starting System Transmission Drive Train	799.9cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC 91 x 62 mm 73 Nm @ 5,500 RPM 46 mm Throttle Body, 2 Siemens [†] VDO injectors Electric CVT, sub-transmission with high, low, park, neutral & reverse Selectable 2w/4w shaft driven with Visco-Lok [†] front differential	Frame Front Suspension Type Travel Rear Suspension Type Travel Front Brake Rear Brake Tires/Front Tires/Rear Wheels	SST RS-Type Double A-arm, forged aluminum upper arm, HPG shocks 8.5 in (216 mm) RS-Type TTI independent, HPG shocks 9 in (229 mm) 2 hydraulic discs 1 inboard hydraulic disc ITP Holeshots ATRs 25 x 8 x 12 in 635 x 203 x 305 mm ITP Holeshots ATR 25 x 10 x 12 in 635 x 254 x 305 mm Center cast aluminum	L x W x H (in) L x W x H (mm) Wheelbase Seat Height Dry Weight Ground Clearance Rack Capacity Towing Capacity Fuel Capacity	86 x 46 x 45 in 2,184 x 1,168 x 1,143 mm 51 in (1,295 mm) 34.5 in (877 mm) 607 lbs (275 kg) 11 in (279 mm) Rear: 35 lbs (16 kg) 1,300 lbs (590 kg) 5.3 US gal (20 L)	Instrumentation Anti-Theft Storage Electrical Lighting DC Outlet Standard Color	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, auto shut off D.E.S.S. (Digital Encoded Security System) Rear storage 1 US gal (3.7 L) Prewired for winch 4 fender mounted Projector Beam headlamps (60W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Yellow	X Package Content Available X Color	Front Kayaba [‡] HPG piggyback shocks with high & low speed compression adjustments, rear KYB HPG shocks with remote reservoir, high & low speed compression adjustments, black center cast aluminum wheels with reinforcement rings, aluminum skid plate, handlebar wind deflector, aluminum taper-profile handlebar with square pad, X package graphics, X package seat cover Black

©2007 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

can-am
THE ULTIMATE RIDE™

